PRODUCTS

Concentrated Low-VOC Stain

Just add water

by Scott Gibson

Eco Hybrid Stain has near-zero levels of volatile organic compounds and offers advantages of both water- and oil-based finishes, says its maker, Eco Chemical. Like a conventional oil-based finish, it penetrates deeply into wood, adheres well, and has good color clarity. And like water-based stains, it forms a durable, vapor-permeable film, is nontoxic and nonflammable, and cleans up with soap and water.

Sold in 5-gallon containers of concentrate, Eco Hybrid Stain is typically mixed with water in a 1-to-3 ratio before application, yielding a total of 20 gallons of stain. The amount of water added can be adjusted to change the degree of opacity.

Pigments in the stains are 100 percent iron oxides, which offer high resistance to UV light and don't chalk or fade, according to the company. Six colors are available: redwood, cedar tone, gold, brown, black, and gray.



Eco Chemical is in the process of establishing a dealer network for Eco Hybrid. For the time being, contractors can purchase the stain (only in 5-gallon containers) by calling Eco Chemical directly. A container costs between \$40 and \$45, so mixed to the usual concentration, it runs about \$2 a gallon.

Scott Gibson is a freelance writer in East Waterboro, Maine.

■ **Eco Chemical,** 800/677-7930, ecochemical.com.



uradek has tweaked its Ultra roofing membrane to create a waterproofing product specifically for use beneath exterior tile installations. Unlike the roofing membrane, Ultra Tiledek has fabric embedded in its surface to promote adhesion with thinset mortar.

The company says the 60-mil PVC membrane is completely compatible with thinset adhesive, can be used in high-traffic areas, is stable in high-heat, high-moisture conditions, and won't degrade. It meets code requirements for use over living spaces, and has passed ANSI and ASTM tests required by the Tile Council of North America and the Terrazzo Tile and Marble Association of Canada.

One hitch is that you can't buy and install the membrane yourself. Ultra Tiledek can be installed only by trained contractors specializing in roof-deck and balcony waterproofing.

The company didn't provide pricing. -S.G.

■ **Duradek**, 800/338-3568, duradek.com/tiledek.

For more information about these products, go to http://exteriorproducts.hotims.com.

Customers want a better view Deliver it with the indoor/outdoor railing system that opens up sightlines with a choice of 3 infills. Get estimate support, get direct shipping and... get a better view. Cables... Cables... Acrylic Glass Banisters & Railings Www.StairCaseandRailingStore.com / Toll Free: 855-365-5387

Go to http://exteriorproducts.hotims.com for more info

Statement of Ownership

Statement of ownership, management and circulation of Professional Deck Builder (publication Number 024-935) filed 9-30-12. Professional Deck Builder is published 7 times a year. Annual subscription rate: free to qualified recipients. The mailing address is Professional Deck Builder, Hanley Wood, LLC, One Thomas Circle NW, Suite 600, Washington, DC 20005. Publisher headquarters address is Hanley Wood, LLC, One Thomas Circle NW, Suite 600, Washington, DC 20005. The publisher is Fred Chandler, One Thomas Circle NW, Suite 600, Washington, DC 20005. The editor is Andy Engel, One Thomas Circle NW, Suite 600, Washington, DC 20005. The managing editor is Laurie Elden, One Thomas Circle NW, Suite 600, Washington, DC 20005. The owners are: Hanley-Wood Holdings, LLC; HW Topco Inc.; One Thomas Circle NW, Suite 600, Washington, DC 20005. Average number of copies per issue during the preceding 12 months were—total number of copies printed: 19,228; mail subscriptions 18,013; sales through dealers and carriers, street vendors, counter sales, and other non-USPS distribution: 22; total paid and/or requested circulation: 18,035; non-requested copies distributed by mail: 290; non-requested copies distributed outside the mail: 393; total non-requested distribution: 700; total distribution: 18,735; copies not distributed: 493; total: 19,228; percent paid and/or requested circulation: 96.3%.

Actual copies of the single issue published nearest to the filing date were—total number of copies printed: 20,031; mail subscriptions 18,014; sales through dealers and carriers, street vendors, counter sales, and other non-USPS distribution: 20; total paid and/or requested circulation: 18,034; non-requested copies distributed by mail: 315; non-requested copies distributed outside the mail: 1,100; total non-requested distribution: 1,430; total distribution: 19,464; copies not distributed: 567; total: 20,031; percent paid and/or requested circulation: 92.7%. I certify that all information furnished on this form is true and complete.

—Fred Chandler, Publisher 9/30/12

PRODUCTS

Acetylated Porch Flooring

Perennial Wood adds to product line

Like Perennial Wood's decking, its tongue-and-groove porch flooring is southern pine treated with a process called acetylation, which alters the cellular structure of wood with heat, pressure, and acetic anhydride. The treatment leaves no toxic materials in the wood, and boards can be painted or stained. The company says the wood is three times more stable dimensionally than unmodified wood and is less likely to shrink, swell, cup, and warp. It's guaranteed against rot, decay, and movement for 25 years.

Perennial Wood decking is available in the Northeast, but the porch flooring is the first Perennial product that will be distributed in the southeastern U.S. It will be sold in North Carolina, South Carolina, and Virginia in lumberyards serviced by Snavely Forest Products.

Flooring will come in 8- and 10-foot lengths in three profiles: $\frac{3}{4}$ inch and $\frac{7}{8}$ inch thick with a $\frac{3^{1}}{8}$ -inch face; and $\frac{29}{32}$ inch thick with a $\frac{5^{1}}{8}$ -inch face.

The company didn't list pricing but said the flooring would be priced at or below the retail price for premium porch flooring made from plastics and wood-plastic composites. – *S.G.*

■ Perennial Wood, 800/530-7495, perennialwood.com.



For more information about this product, go to http://exteriorproducts.hotims.com.